



INVESTOR IN PEOPLE

BEST AVAILABLE COPY

PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

REC'D 01 MAY 2003

WIPO PCT


PCT/GB2003/925

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

Dated

R. Mahoney

24 MAR 2003

The Patent Office

07MAR02 E70136650 D01038
P01/7700 0.00-0205312.2

The Patent Office
Cardiff Road
Newport
South Wales
NP10 8QQ

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

1. Your reference P103855GB/47673

2. Patent application number
(The Patent Office will fill in this part)

0205312.2

3. Full name, address and postcode of the or of each applicant (underline all surnames)

IFR Limited
Longacres House
Six Hills Way
Stevenage
Hertfordshire
SG1 2AN
United Kingdom

Patents ADP number (if you know it)

7434970002

If the applicant is a corporate body, give the country/state of its incorporation

United Kingdom

4. Title of the invention

Testing Mobile Telephone Terminals

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

WITHERS & ROGERS
Goldings House
2 Hays Lane
London
SE1 2HW

Patents ADP number (if you know it)

1776001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (answer 'Yes' if:

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

YES

Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 5

Claim(s) 2 DM

Abstract 1

Drawing (s) 2+2

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77) 1 ✓

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature Winters Rogers Date 05/03/02

12. Name and daytime telephone number of person to contact in the United Kingdom

Jeff K Hogg

0117 925 3030

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least six weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500 505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

P103855GB

TESTING MOBILE TELEPHONE TERMINALS

This invention relates to a method and apparatus for testing a mobile telephone terminal.

Known mobile terminal testers implement most of the communications protocol that a base station would use to communicate with the terminal, and interact with the terminal so as to measure its performance, for example, in terms of bit error rate and modulation quality. These testers are therefore relatively complicated both in terms of their hardware and software.

An object of the invention therefore is to provide a simplified method and apparatus for testing mobile telephone terminals.

This is achieved according to the present invention by using a predetermined transmitted data pattern to trigger a response, preferably, an access request, from the terminal, and analysing the response to assess the performance of the terminal without responding to the terminal. The test apparatus does not therefore need to incorporate the associated hardware or software.

The invention will now be described by way of example with reference to the accompanying drawings, in which:

Figure 1 illustrates a conventional mobile radio test set;

Figure 2 illustrates a test set according to the invention; and

Figure 3 illustrates an alternative embodiment of the invention.

The architecture required for a conventional mobile radio test set, as illustrated in Figure 1, comprises the following:

- (a) The MMI at the top of the tree: This usually includes some form of display to inform the user of the current instrument and test status. Keys allow the user to implement the chosen test.
- (b) Layer 3 protocol: This layer forms messages for the mobile and interprets messages from the mobile.
- (c) Layer 2 protocol: This layer's job is to ensure reliable transmission and reception of messages from/to Layer 3. For example, when sending a message to the mobile a response is usually made. If Layer 2 does not hear this response it will retransmit the message, on the assumption that the original transmission was not successful.
- (d) Layer 1b protocol: A subset of Layer 1. On the downlink this layer takes the Layer 2 blocks and applies channel encoding to aid successful transmission on the air interface. On the uplink the reverse happens and channel decoding is used to reveal the Layer 2 message from the mobile.
- (e) Layer 1a protocol (a subset of Layer 1): On the downlink this layer takes the binary information from Layer 1b and modulates it to give baseband I and Q samples. For the uplink this layer receives IQ samples and demodulates them back to binary values.
- (f) IQ modulator: On the downlink this takes the baseband IQ generated by Layer 1 and forms a signal at the correct carrier frequency using a local oscillator.
- (g) IQ demodulator: The reverse of the IQ modulator - it takes the modulated carrier and derives IQ at baseband.
- (h) RF transmit/receive paths.

When a mobile is first connected to the test set, there needs to be a signal that it can recognise. For GSM this takes the form of the Broadcast Control Channel (BCCH). There are a number of constituent elements to this channel:

- (a) Frequency Control Channel (FCCH)
- (b) Synchronisation Channel (SCH)
- (c) System Information Messages

The mobile uses the FCCH and SCH to synchronise to the test set emulation of a basestation, allowing it to demodulate and interpret the System Information Messages. Once it has done this, it may attempt to register with the test set. This registration process is initiated by the mobile when it sends an Access burst on the Random Access Channel. The test set demodulates the Access burst and responds. A brief series of messages pass between the test set and mobile as they exchange and verify system information.

Once a mobile is registered, it is then possible to initiate a call to/from the mobile which will allow parametric tests of the mobile's transmitter and receiver.

The need to interact in real-time with the mobile leads to a complicated software/hardware architecture.

The invention simplifies the test set architecture by appreciating that a considerable amount of testing can be done by simply getting the mobile to send an Access burst on the Random Access Channel. The invention achieves this with the architecture as illustrated in Figure 2.

The IQ modulator remains with its associated Local Oscillator (LO), but the IQ data applied to it is no longer coming from a conventional Layer 1, 2, 3 architecture. Instead, a fixed Broadcast Control Channel is stored in memory as IQ samples. These are clocked out by an address generator and applied to the IQ modulator.

Alternatively the predetermined pattern may be generated using a subset of the protocol stack for example stored data symbols may be processed by a baseband modulator, which is a subset of Layer 1a, before being applied to the IQ modulator.

The mobile responds to the fixed BCCH by sending an Access burst but it does not get a reply. The test set uses a power detector to determine whether the mobile makes a transmission and this may be indicated to the user on a display.

Alternatively the access burst may be captured by a radio frequency receiver and analysed. The analysis may determine modulation quality, for example.

When the mobile fails to get a reply to its Access burst it will try again a number of times, before searching for another signal.

The information in the stored BCCH tells the mobile the power level at which to transmit its Access burst, and the number of burst retries to perform. So, a number of different BCCH can be stored and selected to test the mobile's power level control.

Placing an attenuator in the downlink would vary the output level from the test set to the mobile. This allows measure of sensitivity - slowly lowering the output power until the mobile no longer transmits Access bursts.

The test set may be connected directly to an antenna connector on the mobile phone using a cable.

An alternative option, rather than cable connection between the test set and the mobile, is to use a coupler, as illustrated in Figure 3.

The coupler makes a connection to the mobile over the air interface rather than through a piece of cable. As such, the coupler and mobile may need to be screened from other signals. This makes sure that the mobile can only hear the test set signal. This approach then allows the test set to verify that the mobile's antenna is functioning correctly.

Thus, comparing the invention with the conventional test sets, the use of a stored downlink data pattern (BCCH) instead of a complete protocol stack, requires a lot less software development and does not require the complex signal processing hardware of conventional test sets.

The test set according to the invention is simpler, cheaper and more robust which makes it suitable for widespread use, for example, in retail outlets which sell mobile telephones.

The retail outlets can then check a mobile to see if it is faulty before returning it to a more expensive repair centre.

The invention has been described above with reference GSM, but there are no reasons why the invention is not applicable to other systems such as Wideband CDMA.

CLAIMS

1. A method of testing a mobile telephone terminal comprising the steps of transmitting to the terminal on a downlink a predetermined data pattern which it will recognise and which will prompt it to transmit an access request on an uplink, and receiving the access request and analysing it to assess the performance of the terminal without responding to the terminal.
2. A method as claimed in claim 1 in which multiple predetermined data patterns are provided for testing the terminal under different operating conditions, each data pattern prompting a different response from the terminal in transmitting an access request.
3. A method as claimed in claim 2 in which said multiple predetermined data patterns are such that they each prompt the terminal to transmit an access request at a different power level.
4. A method as claimed in claim 2 or 3 in which said multiple predetermined data patterns are such that they each specify a different maximum number of times the terminal should send an access request if it receives a response to none of them.
5. A method as claimed in any one of the preceding claims in which said predetermined data pattern is transmitted multiple times at different power levels and the response of the terminal analysed to determine a threshold at which it fails to transmit an access request.
6. A method as claimed in any one of the preceding claims in which said predetermined data pattern is transmitted to the terminal on a cable connection.
7. A method as claimed in any one of claims 1 to 5 in which said predetermined data pattern is transmitted to the terminal over an air interface.

8. A method as claimed in claim 7 in which the air interface is screened from other signals.
9. Test apparatus for testing a mobile telephone terminal, the test apparatus being adapted to transmit a predetermined data pattern on a downlink to prompt a response from the terminal in the form of an access request on an uplink, the test apparatus being adapted to analyse the access request and produce a test result without further responding to the terminal.
10. Test apparatus as claimed in claim 9 which generates multiple predetermined data patterns for testing the terminal under different operating conditions of transmission power level and/or maximum number of access requests to be transmitted if there is no response to any of them.
11. Test apparatus as claimed in claim 9 or 10 which is adapted to vary the power level at which it transmits said predetermined data pattern and to analyse the response to each from the terminal.
12. Test apparatus as claimed in any one of claims 9 to 11 which is connected to the terminal to transmit said predetermined data pattern either by a cable connection or an air interface.
13. A method of testing a mobile telephone terminal substantially as herein described with reference to Figures 2 and 3 of the accompanying drawings.
14. Test apparatus for testing a mobile telephone terminal substantially as herein described with reference to Figures 2 or 3 of the accompanying drawings.

ABSTRACT**Testing Mobile Telephone Terminals**

A mobile telephone terminal is tested by a test set transmitting to the terminal on a downlink a predetermined data pattern which it recognises and which prompts it to transmit an access request on an uplink. The access request is analysed by the test set to assess the performance of the terminal without the test set otherwise responding to the access request from the terminal. Multiple different data patterns may be used such that each prompt the terminal to transmit an access request at a different power level and/or specify a different maximum number of times the terminal should send an access request if it receives a response to none of them.

The predetermined data pattern may be transmitted multiple times at different power levels and the response of the terminal analysed to determine a threshold at which it fails to transmit an access request.

1/2




FIG. 1.

2/2




FIG. 2.




FIG. 3.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.